

CLASSIK812

CHARGER FEATURES

- ✓ 1 or 3 phase models
240/480/600Vac, 50/60Hz
- ✓ Low total cost of ownership
- ✓ Fully automatic
- ✓ Programmable features
- ✓ Wrong battery detection
- ✓ High/low battery voltage detection
- ✓ Overvoltage protection
- ✓ Intelligent safety system
- ✓ Automatic data saving
- ✓ Manual emergency stop button
- ✓ Manual equalize button
- ✓ Automatic equalize



AFFORDABLE
CONVENTIONAL CHARGE



AFFORDABLE FLEET OR RENTAL SOLUTION

When an inexpensive reliable charger is needed, the CLASSIK 812 is the perfect solution. Compact, light and easily serviceable at a price that won't blow your budget, it will offer years of charging while maintaining batteries at optimal performance.

TECHNICAL DATA SPECIFICATION

| MODEL NUMBER | CONVENTIONAL CHARGE | AC CURRENT DRAW 120V (A) | AC CURRENT DRAW 240V (A) | AC CURRENT DRAW 480V (A) | AC CURRENT DRAW 600V (A) | CABINET TYPE |
|---------------------|---------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------|
| CF-LR1-64803-24/100 | 550 | N/A | N/A | 4.5 | 3.6 | T9 |
| CF-LR1-64803-24/160 | 925 | N/A | N/A | 7.2 | 5.8 | T9 |
| CF-LR1-64803-36/140 | 800 | N/A | N/A | 9.5 | 7.6 | T9 |
| CF-LR1-64803-36/160 | 925 | N/A | N/A | 10.8 | 8.7 | T9 |
| CF-LR1-64803-48/120 | 700 | N/A | N/A | 10.8 | 8.7 | T9 |
| CF-LR1-64803-48/160 | 925 | N/A | N/A | 14.4 | 11.5 | T9 |
| CF-LR1-64803-80/80 | 450 | N/A | N/A | 12.0 | 9.6 | T9 |
| CF-LR1-42401-24/100 | 550 | N/A | 15.6 | 7.8 | N/A | T9 |
| CF-LR1-42401-24/160 | 925 | N/A | 25.0 | 12.5 | N/A | T9 |
| CF-LR1-42401-36/140 | 800 | N/A | 32.8 | 16.4 | N/A | T9 |
| CF-LR1-42401-36/160 | 925 | N/A | 37.5 | 18.7 | N/A | T9 |
| CF-LR1-42401-48/120 | 700 | N/A | 37.5 | 18.7 | N/A | T9 |
| CF-LR1-42401-48/140 | 925 | N/A | 43.7 | 21.9 | N/A | T9 |
| CF-LR1-42401-80/80 | 450 | N/A | 41.6 | 20.8 | N/A | T9 |
| CF-LR1-1201P-12/40 | 225 | 6.1 | N/A | N/A | N/A | T5 |
| CF-LR1-1201P-12/80 | 450 | 12.2 | N/A | N/A | N/A | T6 |
| CF-LR1-1201P-24/40 | 225 | 12.2 | N/A | N/A | N/A | T5 |
| CF-LR1-1201P-36/40 | 225 | 15.0 | N/A | N/A | N/A | T5 |
| CF-LR1-1201P-48/30 | 165 | 15.0 | N/A | N/A | N/A | T5 |
| CF-LR1-1201P-80/15 | 80 | 15.0 | N/A | N/A | N/A | T5 |

*Other models available

*Specifications are subject to change

MODEL NUMBER BREAKDOWN

| | | | | |
|------------------------------|---------------|---|----------------|----------------|
| <u>CF</u> | <u>LR1</u> | <u>64803</u> | <u>36</u> | <u>140</u> |
| ↓ | ↓ | ↓ | ↓ | ↓ |
| TECHNOLOGY (Control flux) | CONTROL BOARD | INPUT VOLTAGE/PHASE 64803 (600/480/3PH) 42401 (480/240/1PH) 42403 (480/240/3PH) 1201P (120/1PH) | OUTPUT VOLTAGE | OUTPUT CURRENT |

CABINET DIMENSIONS

(W x D x H in)

| |
|----------------------------|
| T9 ▶ 19.84 x 12.48 x 31.10 |
| T5 ▶ 8.74 x 9.53 x 9.49 |
| T6 ▶ 14.40 x 11.14 x 11.61 |

WARRANTY

- ▶ 3 to 5 year full warranty
- ▶ 5 year power warranty

CLASSIK812

